

# MLE/MLG24PD

## MAYTAG® COMMERCIAL SINGLE LOAD SUPER-CAPACITY STACK DRYER



www.maytagcommerciallaundry.com

### LEGENDARY MAYTAG DEPENDABILITY

Maximizing your equipment investment for over a half century.

### TWO POCKETS IN THE SPACE OF ONE

You can potentially double your dryer income and help eliminate waiting with two dryer pockets in the same floor space as one single-load dryer.

### FOR YOUR CUSTOMERS:

- Extra-Large 7.4 cu. ft. Capacity
- Easy To Use One-Touch Cycle Selection
- High Air Flow For Better Clothes Care
- Time Remaining Display
- Optional Top Off
- Large Window For Convenience

### FOR YOUR OPERATION:

- TurboVent™ — Better Performance On Long Vents
- Advanced Computer Trac® Controls Allow For Easy Programming
- Front Access For Easier Self Service
- Accu Trac® Audit System With Two-Way Data Communication
- Large-Capacity Metal Mesh Lint Filter
- Debit Card Compatibility
- Dual Coin-Drop Option

### BUILT-TO-LAST™ FEATURES:

- Four Roller Suspension With Permanently Lubricated Bearings
- Blower Guard Reduces Service Calls
- Premium Security Vault
- Best Warranty in the Business



### 5 YEARS ON ALL PARTS

For a period from the date of original purchase through the time listed above, the designated parts that fail in normal commercial use will be repaired or replaced free of charge for the part itself, with the owner paying all other costs, including labor, transportation and customs duty. Chemical damage is excluded from all warranty coverage. See complete warranty for details.



### MICROPROCESSOR COIN-DROP

DRYER SPECIFICATIONS	
MODEL	MLE/MLG24PD
<b>MOTOR</b>	
Single-phase, thermoprotected against overload, auto-reset	•
HP (kw)	1/8 (.25)
<b>CAPACITY</b>	
Cu. ft. (liters)	7.4 (209.5)
<b>AIRFLOW</b> — cfm (cmm)	
Gas models — per pocket	230 (6.5)
Electric models — per pocket	215 (6.1)
<b>TUMBLE SPEED</b>	
RPM	50 ± 1.5
<b>ELECTRICAL REQUIREMENTS</b>	
MDE model — voltage	240V/60Hz
MDG model — voltage	120V/60Hz
Export models — voltage	220-240V/50 Hz
<b>BREAKER/FUSE REQUIREMENTS</b>	
Electric model — domestic (each drying chamber)	30
Electric model — export (one terminal block per stack)	40
Electric model — Canada (one terminal block per stack)	60
Gas models — (one power cord per stack)	20
<b>APPROXIMATE OVERALL DRAW</b> — watts	
Domestic model — per pocket	6,000
Export models — per pocket	5,000
<b>EXHAUST DUCT DIAMETER</b>	
In. (mm)	4 (101.6)
<b>ELECTRONIC BURNER IGNITION</b>	
MDG models	•
<b>GAS RATING</b>	
MDG models — BTU/hr. (kcal/hr.)	24,000 (6,048)
<b>GAS INLET</b>	
MDG models — in.	3/8 N.P.T.
<b>AUTOMATIC PRESSURE REGULATOR</b>	
MDG models	•
<b>ADJUSTABLE LEVELING LEGS</b>	
MDG models	•
<b>APPROXIMATE WEIGHT</b>	
Crated — lbs. (kg)	325 (147.4)
Uncrated — lbs. (kg)	300 (136.1)
<b>DIMENSIONS</b>	
Width — in. (mm)	27 (685.8)
Depth — in. (mm)	29.5 (749.3)
Height — in. (mm)	76.75 (1949)
See specific instructions for proper installation. Because of continuous product improvement, Maytag reserves the right to change specifications without notice.	

LAUNDRY SOLUTIONS  
YOU CAN *DEPEND* ON.